



WINSAFE USB2.0 1080P Webcam WS-M02



WINSAFE WS-M02 is cost-effective USB2.0 1080P HD camera, built-in omnidirectional sound absorption and noise reduction microphone, clear communication. High-definition lens, good light transmission, true color reproduction, effectively reduce image distortion. No driver need, easy to connect, it can be used on online teaching, live broadcast, video conference, video chat, smart TV external device.



Feature

- F23 million high-definition image sensor with an effect of 1932 x 1088
- Using high-definition lens, good light transmission, true color reproduction, effectively reduce image distortion
- Support audio collection, built-in omnidirectional sound absorption and noise reduction microphone, clear communication
- Make fine adjustments and correct light according to lighting conditions
- Color optimization engine, automatic color compensation, skin tone adjustment function
- Standard UVC/UVA protocol, driver-free, plug and play
- Support Windows / Android / Linux system
- Support H.264 and MJPEG image formats, Maximum support 2MP/30FPS image resolution
- Can rotate 360 degrees left and right, and the head can be adjusted up and down
- Used for online streaming, live broadcast, video conference, video chat, smart TV external device.

HD Video Camera

High Definition image quality, resolution up to 2 Megapixel, 1920*1080

Built-in Microphone

Plug And Play, Multi-party Connections

Support Windows / Android / MAC / Linux system.

Windows

Android

MAC

Linux

Technical Specification

Model No.	WS-M02
Image Sensor	1/2.9 F23 HD CMOS Sensor
Effective Pixel	1932(H) x 1088(V)
Video Steam	H.264: 1920x1080/1920x720/640x360 MJPEG: 1920x1080/1920x720/640x360 YUV: 640x360
Video format	AVI
Output format	YUY2
Fram rate	25fps/30fps
Shutter	Auto
Protocol	UVC/UVA
OSD	No
S/N	Above 50dB
Audio	Built-in Microphone
Video output	USB
VM	180M/bmp
USB Cable	USB2.0 , 1.5M
System Support	Support XP2, WIN7, WIN8, WIN10, MAC and so on.
TWAIN	Support Different Video Conference System
Power Supply	DC5V/160mA ±6mA
Working Temperature	-20°C - 60°C
Net Weight	110g
Gross Weight	160g
Size	9.92cm x 3.05cm x 2.64cm
Package	15.5cm x 9cm x 5cm
Product specification are subject to change without notice	